

MATERIAL SPECIFICATIONS

DURACOUSTIC

Product	DURACOUSTIC
Thickness	8 mm
"R" value	0.52
Mass	87 oz / sq.yd.
Density	22 lbs / cu.ft
Tensile	214. N/5cm.
Content	100 % Virgin SBR & Rubber
Material Analysis	Minimum 85% recycled rubber
Roll size	12 sq.yd.
Roll Weight	65 lbs
Roll Width	54 in.
Roll Length	24. ft.
Roll Diameter	11 in.
Coverage	108 sq.ft.
Acoustical Value	IIC 57 / ASTM E492 - Impact Insulating Class STC 70 / ASTM E-90 - Sound Transmission Class
Moisture barrier	N/A
Moisture Transmission Rate	N/A
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Recommended
LEED	Contributes up to 5 Credits
Flamability	PASS Pill Test / ASTM D2859 Class 1 / ASTM E 648 Radiant Panel Test As an assembly with a Class 1 commercial carpet
Application	For multiple application of Sound Control

Dura Undercushions Ltd.

T: (514) 737-6561

(800) 295-4126

F: (514) 342-7940

E: info@dura-undercushions.com

W: www.duracushion.com