

MATERIAL SPECIFICATIONS

PROTECTOR

Product	PROTECTOR
Thickness	5 mm
"R" value	0.46
Mass	54 oz / sq.yd.
Density	22 lbs / cu.ft
Tensile	214. N/5cm.
Content	Minimum 85% recycled rubber bonded with synthetic rubber
Roll size	20 sq.yd.
Roll Weight	68 lbs
Roll Width	54 in.
Roll Length	40. ft.
Roll Diameter	11 in.
Coverage	180 sq.ft.
Acoustical Value	FIIC 73 / ASTM E 1007- Impact Sound Transmission * * With a 35oz carpet
Moisture Protection	N/A
Water Vapor Transmission Rate	N/A
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Suitable for radiant heated floor
LEED	Contributes up to 6 Credits
Flamability	PASS Pill Test / ASTM D2859 Class 1 / ASTM E 648 Radiant Panel Test As an assembly with a Class 1 commercial carpet
Application	Heavy Commercial Carpet Cushion Class 1,2 & 3

Dura Undercushions Ltd.

T: (514) 737-6561
(800) 295-4126

F: (514) 342-7940

E: info@dura-undercushions.com

W: www.duracushion.com