

MATERIAL SPECIFICATIONS

SUPER DURA

Product	SUPER DURA
Thickness	10 mm
"R" value	0.88
Mass	106 oz / sq.yd.
Density	22 lbs / cu.ft
Tensile	214. N/5cm.
Content	Minimum 85% recycled rubber bonded with synthetic rubber
Roll size	10 sq.yd.
Roll Weight	66 lbs
Roll Width	54 in.
Roll Length	20. ft.
Roll Diameter	11 in.
Coverage	90 sq.ft.
Acoustical Value	FIIC 78 / ASTM E 1007- Impact Sound Transmission * * With a 35oz carpet
Moisture Protection	N/A
Water Vapor Transmission Rate	N/A
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Suitable for radiant heated floor
LEED	Contributes up to 6 Credits
Flamability	PASS Pill Test / ASTM D2859 Class 1 / ASTM E 648 - Radiant Panel Test As an assembly with a Class 1 commercial carpet
Application	Residential & Light Commercial

Dura Undercushions Ltd.

T: (514) 737-6561

(800) 295-4126

F: (514) 342-7940

E: info@dura-undercushions.com

W: www.duracushion.com